



- Surface Mount (Wall or Ceiling)
- White Polycarbonate Body
- Translucent Polycarbonate Cover
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP41
- 25m viewing distance
- ISO legends as standard
- DDP (Deep Discharge Protection)
- Samsung LED's

A stylish and compact Double Sided LED Exit Sign suitable for either wall or ceiling mounting. The unit is available in either a Switchable Maintained/Non-Maintained or a DALI Self-Test version. The unit is supplied with a Plexi glass screen printed legend plate which offers an impressive 25m viewing distance.

The legend panels are available in either Arrow Up (AU), Arrow Down (AD) or Arrow Left/Right (ALAR). Please note that all legends are single sided, apart from the ALAR which are double sided. The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

Order Codes

CE1S/2W/M3/**	Switchable Maintained	** Please specify legend
CE1S/2W/DA/**	DALI Self-Test Maintained via Mains Switch	required AU, AD, or ALAR

Technical Details:

	CE1S/2W/M3	CE1S/2W/DA
Mains Supply	230-240V AC 50/60 Hz	
Power Rating	44mA $\lambda = 0.6$	40mA $\lambda = 0.6$
Duration	3 Hours	
Recharge Period	12 Hours – Energy saving electronic charger	
Battery Size & Type	6.4V 1.6Ah LiFePO4 Cells	9.6V 1.5Ah LiFePO4 Cells
Charge Current	0-400mA Dual Rate	0-150mA Dual Rate
Ingress Protection Rating	IP41	
Class	Class II	
Weight	0.94Kg	0.95Kg