



- Suitable for Integral or Remote Applications
- Interoperable with other IQRF Products
- Compatible with all DALI Emergency Products
- Simple Installation
- Compatible with LiteWork Commissioning Tool
- Transmits at Long Range 868Mhz
- Compatible with LiteMesh Operating System

The LiteWay forms part of the LiteMesh suite of wireless products. This unit connects the mesh to the cloud and subsequently to the LiteFace user portal.

The mesh operates IQRF's 868Mhz frequency, which achieves up to 50m range between nodes. This is perfect for emergency lighting and continuity of the mesh. IQRF's technology provides a scalable, robust and secure network.

The module is capable of being used for integral, or remote applications, thanks to its removable strain relief terminal covers.

Order Codes

LITEWAY/BASIC LiteMesh Compatible Wireless IoT Gateway

Technical Details:

Input Voltage	230-240V AC 50/60Hz
Network Protocol	IQRF, LiteMesh, 868Mhz
Range	Up to 500m line of sight and up to 100m within a building
IoT Connectivity	via Standard Ethernet interface (RJ45)
Security	Multilayer, AES-128, Dynamic Keys
Interface	Bluetooth 4.0, WiFi and Ethernet, Full Gigabit (10/100/1000) Interface.
Ports	Two USB 2.0, One Ethernet