



- 115 ° Open Area or Corridor Optic Options
- Standard, Self-Test and DALI Options Available
- High Output - Up to 268 Delivered Lumen
- 185mm Diameter x 42mm Depth
- White or Black 30% Gloss Finish
- Contains Kitemarked (HJT) Control Gear
- Non-Maintained Operation

The MPR/NM3 is a surface mount standalone emergency LED luminaire which can incorporate our open area or corridor 3W LEDs. The unit is for non-maintained.

The main LED is driven at 700mA and provides either 268 delivered lumen with the open area lens or 266 delivered lumen with the corridor lens.

### Order Codes

**MPR/\*\*/W/NM3** White (RAL9016) Emergency Device

**MPR/\*\*/B/NM3** Black (RAL9005) Emergency Device

\*\* = OA for Open Area Lens and CO for Corridor Lens

### Spacing Table with Open Area Lens:

Mounting Height	To Wall		Between Fittings	
	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux
2.5m	3.9m	3.6m	8.2m	7.6m
3.0m	4.5m	4.1m	9.4m	8.7m
4.0m	5.5m	4.8m	11.8m	10.9m
5.0m	6.4m	5.0m	14.0m	12.6m
6.0m	6.9m	3.1m	16.0m	13.3m
8.0m	6.0m	-	18.9m	8.5m

### Technical Details:

Input Voltage	230-240V AC 50/60Hz	Lumen Output (OA)	268 Delivered Lumen
Power Rating	51mA - $\lambda = 0.51$	Lumen Output (CO)	266 Delivered Lumen
Charge Current	200mA Nominal	Battery Type	3.6V 4.5Ah NiCd
Duration	3 Hours	Mains Input Termination	0.75mm to 2.5mm Cable
Recharge Period	24 Hours	Ingress Protection	IP20
Light Source Colour Temperature	6000K	Dimensions	Ø 185mm x 42mm
Weight	1.1Kg	Ta Max	25 °
Beam Angle (OA)	115 °	Beam Angle (CO)	155 ° x 115 °